



Transmit



Recieve



Decode



Control

**Universal Receiver RCU01 (2-Channel)****Baseline**

The RCU01 is a 2-channel receiver which is universally applicable. It can be operated both with low- and mains voltage.

The receiver can memorise up to four transmission codes per channel. Every channel can be programmed with different operating modes.



RCU01-XX02M-01

**Technical Details**

Coding	not necessary, transmission code is memorized
Channels	2
Power Supply	12-24 V DC or 230 V AC
Control	Pulse (1 sec.) ON/OFF (toggle mode / 1-button-control) Timer (30 sec., 3 min.) Dead man's mode (continuous operation) Awning-control ON/OFF (2-button-control)
Output	2 floating relay contacts
Max. Contact Duty	230 V AC / 1,800 VA 30 V DC / 3 A / 120 W
Degree of Protection	IP65
Operating Temperature	-20 °C to +60 °C
Dimensions	70 x 162 x 38 mm

**Scope of Delivery**

- Universal Receiver
- Rod Aerial (external)
- Mounting Material
- Operating Manual

**Models**

Product Key	Description	Frequency
RCU01-4102M-01	Universal-Reciever	433,92 MHz
RCU01-5002M-01	Universal-Receiver	868,30 MHz

Connection Diagram

