

APC01 Control Center

bidi

The Control Center APC01 represents the smart control hub of an Easywave building installation.

The integrated radio module enables the control of up to 128 Easywave, Easywave neo and secwave devices with an Android or Apple smartphone or tablet.

The following functions are available:

- Creating scenes
- Time-controlled execution of switching commands
- Logical linking of sensors and actuators
- Astro function
- Push notifications
- Integration of Amazon Alexa *)
- Weather data as a trigger for scenes
- Heatingcontrol
- Remote access

Individual functions may be chargeable!



APC01ENS5031A01-21K

Technical specifications

Coding	Easywave Easywave neo (server) secwave
Frequency	868.30 MHz
Radio inputs	
Easywave	unlimited
Easywave neo	128
secwave	128
Radio outputs	
Easywave	128
Easywave neo	128
secwave	128
Power consumption	max. 3.5W (5V 2A)
Interfaces	1x 100 MBit/s BaseT Ethernet port 2x USB Wifi 802.11 b/g/n
Processor	Cortex A7 Quad Core
Main memory	1 GB
Flash	4 GB
Dimensions (W/L/H)	120/120/30 mm
Color	black, mat

Connections



Scope of delivery

- APC01 Control Center
- Ethernet cable (CAT 5)
- Plug-in power supply for 230V Schuko socket
- Operating Manual

Models

Product numbers	Description
APC01ENS5031A01-21K	Easywave Control Center, Easywave neo, server for Easywave CCapp, 128 serial numbers, black

*) Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.