

RT21 Hand transmitter

Transmitter-learns-transmitter (TLT)



The RT21 hand transmitter is available in a 1-channel or 2-channel version.

This variant features a transmitter-learns-transmitter (TLT) function, which allows the serial number to be transferred from one RT21 (TLT) to another RT21 (TLT). By transferring the serial number, both transmitters always trigger the same function in the receiver. Any number of transmitters can be coded the same way.

An easily visible LED lights up when the battery needs to be changed.



RT21E5002B00-K

RT21E5001B00-K

Technical specifications

Coding	Easywave
Frequency	868.30 MHz
Channels	1 or 2
Range	typically 150 m in good free-field conditions
Power supply	1x 3V-battery, CR2032
Operating indicator	LED
Operation	transmission lasts as long as the button is pressed (maximum 36 seconds)
Operating temperature	-20 °C to +60 °C
Dimensions (W/L/H)	36/55/16 mm
Weight	17 g (including battery)
Color	anthracite similar RAL 7016

Scope of delivery

- Hand transmitter incl. battery
- Programming connector
- Operating manual

Accessories (optional)

- ACC-CON-01
- 3-pole pin header, grid 2.54



Models

Product number	Description
RT21E5001B00-K	Hand transmitter, Easywave, 1x PULSE, transmitter-learns-transmitter, anthracite
RT21E5002B00-K	Hand transmitter, Easywave, 2x PULSE, transmitter-learns-transmitter, anthracite